GYROPALETTE® RANGE

The world reference of automated riddling

Quadra Gyropalette®



RIDDLING CAPACITY:

100 000 to 130 000

standard 75 cl bottle per year.

STRONG POINTS



Compatible with all TSR® riddling containers and boxes.



Modular machine & compatible with the Vertical Duo.



The cradles are articulated at the ends without a central support.











Chassis and cages made of hot galvanised steel, electrical and mechanical high quality components, resistance to cellar humidity, limited maintenance.

PRODUCTIVE

2 cradles with 2 independently rotating cages (per 1/16 turn). 4 cages mounted on 4 large diameter ball bearing supported, orientiation crown rotated by 4 sealed electric gear motors.

PRECISION

Inclining to a precise degree by a very robust system, screw-nut motorised system common to the cradles which are linked by small rods.

LOW CONSUMPTION

Very good mechanical efficiency of the rotating and tilting movements: 5 x 0,37 kW motors.

EQUIPMENT OPTIONS



Cages

Choose the cages adapted to your cellar and your process (open, door or automatic cage).



The vibration option allows to optimize your riddling cycle with a benefit effect in the evolution of the deposit located in the bottle.



Installation

Possibility to install several Gyropalette® Quadra side by side or back to back.

CONTROL

The riddling controler ACAI V4 allows to drive one or severals Gyropalette®.

Available in standard or multigroup

Remote supervision Exist in coffret or in cabinet shape



Create your own riddling programs with the Gyroprog® software (Windows® compatible). Once created, transfer the riddling program via a USB dongle in the Gyropalette® controller.

DIMENSIONS

4020

Loading 1095

Unloading

Loading/unloading by forklift with a minimum capacity of 1600 kg

> Door cage in level 1 and open cage in level 2 Door cage in level 1 and automatic cage in level 2 DEVICE Height 3874 Width 4020 4020 Depth 1340 1340 Depth with cage 1584 1524 Depth with box 1882 1782 RIDDLING Height 4400 4400 Depth 2200 HANDLING Loading height 2800 2800 Loading height + box 3791 3791 Unloading height 2950 3909 Unloading height + box 4120 5200 LAYOUT Aisle width 5500 5500

5.8-EN_0625 - Non contractual document